

Śruba mocująca obrotowo-wychylna LBO (APLB)



YOKE



Produkt	Rozmiar	DOR kg	Waga kg
8-211-003G	M8	300	0,2
8-211-006G	M10	630	0,3
8-211-010G	M12	1.000	0,5
8-211-012G	M14	1.200	0,5
8-211-015G	M16	1.500	0,5
8-211-020G	M18	2.000	1,3
8-211-025G	M20	2.500	1,3
8-211-040G	M24	4.000	1,4
8-211-042G	M27	4.000	2,8
8-211-050G	M30	5.000	3,1
8-211-070G	M36	7.000	3,3
8-211-080G	M36	8.000	5,8
8-211-100G	M42	10.000	6,3
8-211-150G	M42	15.000	10,8
8-211-200G	M48	20.000	11,6

Dopuszczalne Obciążenie Robocze APLB

Produkt	Średnica gwintu	DOR										
		0°	0°	90°	90°	0-45°	45-60°	2	0-45°	45-60°	3-4	3-4
8-211-003G	M 8	0,30	0,60	0,30	0,60	0,42	0,30	0,30	0,63	0,45	0,30	0,30
8-211-006G	M10	0,63	1,26	0,63	1,26	0,88	0,63	0,63	1,32	0,95	0,63	0,63
8-211-010G	M12	1,00	2,00	1,00	2,00	1,40	1,00	1,00	2,10	1,50	1,00	1,00
8-211-012G	M14	1,20	2,40	1,20	2,40	1,70	1,20	1,20	2,50	1,80	1,20	1,20
8-211-015G	M16	1,50	3,00	1,50	3,00	2,10	1,50	1,50	3,10	2,20	1,50	1,50
8-211-020G	M18	2,00	4,00	2,00	4,00	2,80	2,00	2,00	4,20	3,00	2,00	2,00
8-211-025G	M20	2,50	5,00	2,50	5,00	3,50	2,50	2,50	5,20	3,70	2,50	2,50
8-211-040G	M24	4,00	8,00	4,00	8,00	5,60	4,00	4,00	8,40	6,00	4,00	4,00
8-211-042G	M27	4,00	8,00	4,00	8,00	5,60	4,00	4,00	8,40	6,00	4,00	4,00
8-211-050G	M30	5,00	10,00	5,00	10,00	7,00	5,00	5,00	10,50	7,50	5,00	5,00
8-211-070G	M36	7,00	14,00	7,00	14,00	9,80	7,00	7,00	14,70	10,50	7,00	7,00
8-211-080G	M36	8,00	16,00	8,00	16,00	11,20	8,00	8,00	16,80	12,00	8,00	8,00
8-211-100G	M42	10,00	20,00	10,00	20,00	14,00	10,00	10,00	21,00	15,00	10,00	10,00
8-211-150G	M42	15,00	30,00	15,00	30,00	21,00	15,00	15,00	31,50	22,50	15,00	15,00
8-211-200G	M48	20,00	40,00	20,00	40,00	28,00	20,00	20,00	42,00	30,00	20,00	20,00



Produkt	Rozmiar	Wymiary w mm										Waga kg/pce	Mom. obr. Nm	zest. nap.
		A	B	C	D	E	F	G	H	S	SW			
8-211-003G	M8 x 1,25	30	35	35	10	11	85	55	29	6	13	0,20	30	8-P211-003
8-211-006G	M10 x 1,50	30	35	36	10	16	85	55	29	6	17	0,30	60	8-P211-006
8-211-010G	M12 x 1,75	33	37	44	14	18	98	57	36	8	19	0,50	100	8-P211-010
8-211-012G	M14 x 2,00	33	37	45	14	21	98	57	36	10	22	0,50	120	8-P211-012
8-211-015G	M16 x 2,00	33	37	46	14	24	98	57	36	10	24	0,50	150	8-P211-015
8-211-020G	M18 x 2,00	50	54	57	17	26	140	82	44	12	30	1,30	200	8-P211-020
8-211-025G	M20 x 2,50	50	54	57	17	30	140	82	44	12	30	1,30	250	8-P211-025
8-211-040G	M24 x 3,00	50	54	59	17	36	140	82	44	14	36	1,40	400	8-P211-040
8-211-042G	M27 x 3,00	60	65	79	23	38	170	99	62	17	41	2,80	400	8-P211-042
8-211-050G	M30 x 3,50	60	65	81	23	48	170	99	62	17	46	3,10	500	8-P211-050
8-211-070G	M36 x 4,00	60	65	88	23	54	178	99	65	22	55	3,30	700	8-P211-070
8-211-080G	M36 x 4,00	77	85	101	27	62	225	124	78	22	55	5,80	800	8-P211-080
8-211-100G	M42 x 4,50	77	85	104	27	72	225	124	78	24	65	6,30	1.000	8-P211-100
8-211-150G	M42 x 4,50	95	104	112	36	63	256	158	86	24	65	10,80	1.500	8-P211-150
8-211-200G	M48 x 5,00	95	104	120	36	72	259	158	90	27	75	11,60	2.000	8-P211-200